

# ELITE series

- 25mm Silk Dome Tweeter
- Fully Machined Removable Aluminum Tweeter Housing
- Dampened Polypropylene Cone
- Precision Cone Control Dual Roll Rubber Surround
- Powder Coated Diecast Aluminum Basket
- Midbass Enhancement EQ Adjustment
- 24dB External Audiophile Grade Crossover
- Three Position Tweeter Level Adjustment
- Dual Stage Optical Tweeter Protection Circuitry
- Integrated Phase Plug
- Interwoven Tinsel Leads
- High Temperature CAE/CAD Motor Structure



|                    | <i>Elite.65cs</i>    | <i>Elite.cs1t</i>    |
|--------------------|----------------------|----------------------|
| Size               | 6.5"                 | 25mm                 |
| Power Handling     | 150w RMS - 300w PEAK | 100w RMS - 200w PEAK |
| Impedance          | 4 Ohms               | 4 Ohms               |
| Frequency Response | 50Hz to 20kHz        | 2.5Hz to 20kHz       |
| Mounting Depth     | 2.54" - 64.6mm       | .81" - 20.6mm        |
| Cut Out Diameter   | 5.73" - 145.5mm      | 1.84" - 47mm         |
| Overall Diameter   | 6.53" - 166mm        | 2.14" - 54.4mm       |